

# 8' PREDATOR

You're always ahead... with a Modern behind!

For more information or to locate a dealer call 1-888-404-8908



# MODERN AG PRODUCTS




Quick Attach Lift Type  
shown Cat. 4 w/Clutch

## Features:

- 1/2" gearbox plate
- Available in pull type & quick attach lift
- Cylinder and hoses are standard on pull type
- Heavy duty stump jumpers & slip clutch protected
- Laminated tailwheels
- Solid 3/16" (7 Gauge) Deck
- Quick Attach
- 3/4" A Frames - QA
- Cat 2. Hitch Lift Type

**HOT DIPPED  
GALVANIZED  
DECK &  
FRAME**

**RUBBER  
GUARD  
STANDARD**



**FRONT &  
REAR CHAIN  
GUARDS  
OPTIONAL**

**THE 8' PREDATOR IS A CAT. 2 HITCH WITH A 150HP  
TRANSFER GEARBOX W/TWO 95 HP OUT BOARD GEARBOXES.**



## RED DOUBLE DIAMOND

Provides a 5 year limited warranty on gearbox and  
10 year limited warranty on deck rust thru.  
(Super Predator, Predator & Super Highway Special series only)



Smooth underdecks make for  
more efficient mowing and less  
area for rust to begin.



**CUTTING  
WIDTH  
96"**

Pull Type shown  
Cat. 5 CV driveline

Aircraft Tires Available  
on Pull Type Only

\* Gearbox ratings based on field performance. \*\* The Galvanized gloss level could vary from unit to unit. Modern Ag Products reserves the right to make changes and/or improvements in design and construction of parts or machines shown herein without notice or obligation.

## SPECIFICATIONS

Cutting Width..... 96"  
Transport Width ..... 102"  
Overall Width..... 102"  
Overall Length..... 97"  
Overall Height ..... 2" - 15"  
Blade Overlap ..... 3"  
Jackstand..... Standard  
Hitch ..... QA Cat. II or Clevis  
Blade Carrier..... Pan Stump  
Jumpers  
Horsepower Required (min):  
Lift..... 50 hp  
Pull..... 45hp

Main Gearbox  
or Divider Box\* ..... 150 hp  
Outboard Gearbox  
or Center & Wings\* ..... 95 hp  
Output Shaft Diameter ... 2-3/8"  
Cut Capacity..... 3"  
Blade Tip Speed:  
540 ..... 15,847 FPM  
1000 ..... 15,847 FPM  
Driveline Size:  
Pull Type ..... Pull-Cat. 5 CV w/  
Slip Clutch  
QA Lift Type ..... QA -Cat. 4  
w/Clutch

Deck Thickness ..... 3/16"  
Side Skirt ..... 1/4" x 8"  
Front Safety Deflectors .. Chain Option  
Rear Safety Deflectors:  
Rubber Guard Standard with Chain Option  
Weight (Approx): ..... QA 1975 lbs.  
Pull 2370 lbs.  
Standard Tires..... Laminated  
600 x 9  
Dual Tailwheels (Pull Type) Option  
Hydraulic Level  
Lift (Pull Type)..... Standard