

ROAD DRAGON

You're always ahead... with a Modern behind!
For more information or to locate a dealer call 1-888-404-8908



MODERN AG PRODUCTS



**HOT
DIPPED
GALVANIZED**

The Road Dragon by Modern is the easiest way to smooth your driveway. Absolutely excellent for filling potholes, washed areas, low spots, washboard areas and recovering gravel. Manicure your roadbed while putting the crown back on your driveway to help shed water and reduce gravel expense. Quality built hot dipped galvanized frames for years of trouble-free use. Hot dipped galvanizing always extends the life of your investment.

ROAD DRAGON GRADER				
SPECIFICATION	5' ROAD DRAGON	6' ROAD DRAGON	7' ROAD DRAGON	8' ROAD DRAGON
Hitch	Cat. I Quick Hitch	Cat. I Quick Hitch	Cat. I & II Quick Hitch	Cat. I & II Quick Hitch
Working Width	60"	72"	84"	96"
Overall Width	64.50"	76.25"	88"	100"
Overall Length	45"	45"	54.25"	54.25"
Side Panel Height	13 3/16"	13 3/16"	15 3/16"	15 3/16"
Side Panel Length	45"	45"	45"	45"
Side Panel Thickness	1/4"	1/4"	1/4"	1/4"
Front Beam	3"x3"x1/4"	3"x3"x1/4"	3"x3"x3/8"	3"x3"x3/8"
Rear Beam	3"x3"x1/4"	3"x3"x1/4"	3"x3"x3/8"	3"x3"x3/8"
Skid Shoes	1/2"x2" Replaceable	1/2"x2" Replaceable	1/2"x2" Replaceable	1/2"x2" Replaceable
Front Cutting Edge	1/2"x6" Heat Treated-Reversible	1/2"x6" Heat Treated-Reversible	1/2"x6" Serrated, Heat Treated	1/2"x6" Serrated, Heat Treated
Rear Cutting Edge	1/2"x6" Heat Treated-Reversible	1/2"x6" Heat Treated-Reversible	1/2"x6" Heat Treated-Reversible	1/2"x6" Heat Treated-Reversible
Tractor HP Rating	20hp (min)-50hp (max)	25hp (min)-60hp (max)	30hp (min)-80hp (max)	35hp (min)-120hp (max)
Weight (LBS)	475 lbs	525 lbs	708 lbs	765 lbs
Galvanized	Yes	Yes	Yes	Yes

SPECIFICATIONS

- Cat. I QA Hitch on 5' & 6' models
- Cat. I & II QA Hitch on 7' & 8' models
- 5' & 6' models have two 6" heat-treated reversible cutting edges
- 7' & 8' models have a HD 6" heat-treated serrated front cutting edge & a reversible 6" rear heat-treated cutting edge for tough, hard packed driveways
- Side plates are made of 1/4" steel on all models
- 5' & 6' models have 3X3X1/4" front & rear beams for stability and strength
- 7' & 8' models have 3X3X3/8" front & rear beams creating added strength for use on larger tractors
- HD bolt on replaceable 1/2" skid shoes on all models
- All units are continuously welded for substantial added strength
- All models are completely hot dipped galvanized for extended life

