## SUPER SUNSHINE 5', 6' & 7'

You're always ahead... with a Modern behind! For more information or to locate a dealer call 1-888-404-8908





Splined input shaft Slip clutch Standard.

## Features:

- New heavy duty 3/8" **Gearbox Plate**
- Heavy duty stump jumper and laminated tailwheel
- Protected by a splined input shaft slip clutch standard
- Solid top weld
  New smooth rounded rear deck
- Heavy duty tailwheel bracket and boom
- Double steel wall top edge
- · One piece body with smooth top

Gearbox ratings based on field performance.

DIAMOND

- Upgraded 65 hp gearbox rating with 2"-15 spline output shaft
- Available Quick Attach
- 3/8" A Frames 3pt.
- 1/2" A Frames QA
- · Cat. 1 Hitch



RUBBER **GUARD** STANDARD

FRONT & **REAR CHAIN** GUARDS OPTIONAL



**WIDTH** 6N"

5' CUTTING

6' CUTTING

**WIDTH** 

7' CUTTING **WIDTH** 



QA Hitch shown



3pt Hitch

shown

Smooth underdecks make for more efficient mowing and less area for rust to begin.

SUPER SUNSHINE GEARBOXES HAVE A HEAVY-DUTY 2" 15 SPLINE OUTPUT SHAFT FOR LONGER LIFE AND BETTER CUT CAPACITY. THE SUPER SUNSHINE IS A LONG LASTING CAT. 1 HITCH CUTTER WITH A CAT. 3 DRIVELINE.

**BLUE DOUBLE DIAMOND** 

10 year limited warranty on deck rust thru.

\*\* The Galvanized gloss level could vary from unit to unit. Modern Ag Products

reserves the right to make changes and/or improvements in design and construction of parts or machines shown herein without notice or obligation

Provides a 3 year limited warranty on gearbox and

## **SPECIFICATIONS**

Cutting Width.......... 60" - 72" - 84" Transport Width ...... 65" - 75" - 88" Overall Width........... 65" - 75" - 88" Overall Length.......... 100" - 106" - 122" Cutting Height . . . . . . . . 2" - 10" Hitch . . . . . Cat. I 3 PT & Quick Attach Blade Carrier . . . . . . . Pan Stump **Jumpers** Quick Attach..... Option

Horsepower Required (min): 72".... 30 hp 84"..... 40 hp Gearbox Rating\* ...... 65 hp Cut Capacity........... 2.5" Blade Tip Speed: 60"..... 16,519 FPM 72"......14,995 FPM 84"......17,300 FPM Driveline Size..... Cat. 3 w/Slip Clutch Deck Thickness . . . . . . . 3/16" Slip Clutch Protection.... Standard Front Safety Deflectors .. Chain Option Rear Safety Deflectors: Rubber Guard Standard with Chain Option Weight (Approx)...... 725 lbs. - 865 lbs. - 1189 lbs. Standard Tires..... Laminated Side Skirt . . . . . . . . . . . . . 1/4" x 8"